



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/19/2023

 12.5
 04/14/2023
 1327200-00048
 Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Vertrel™ MCA specialty fluid

Product code : D10260094

SDS-Identcode : 130000000634

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent

Restrictions on use : For professional and industrial installation and use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Eye irritation : Category 2B

Specific target organ toxicity : 0

- single exposure

Category 3

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H320 Causes eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling.





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue ringing

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
1,1,1,2,2,3,4,5,5,5-	138495-42-8	>= 50 - < 70
Decafluoropentane		
Trans-Dichloroethylene	156-60-5	>= 30 - < 50

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

May cause cardiac arrhythmia.

Skin contact may provoke the following symptoms:

Dermatitis Irritation Pain

superficial burning sensation

Itching Redness

Swelling of tissue

Rash Discomfort

Eye contact may provoke the following symptoms

Pain tearing

Swelling of tissue

Redness

Impairment of vision

Inhalation may provoke the following symptoms:

Unconsciousness Drowsiness

Lack of coordination

confusion Dizziness

Central nervous system depression

Effects of breathing high concentrations of vapor may include:

Tiredness Drowsiness

central nervous system effects

Convulsions

Adverse effects from repeated inhalation may include

central nervous system effects

Aspiration may cause pulmonary edema and pneumonitis.

Causes eye irritation.

May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Because of possible disturbances of cardiac rhythm, ca-

techolamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with spe-

cial caution.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Vertrel™ MCA specialty fluid



Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Hydrogen fluoride carbonyl fluoride Carbon oxides Chlorine compounds

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Vertrel™ MCA specialty fluid



Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Do not expose drums to direct heat or temperature above

46°C (115°F) to avoid pressurizing and possibly distorting the

drums.

Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller containers where adequate ventilation can be used to manage

the exposure.

Keep in properly labeled containers.

Store locked up.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage tem-

perature

< 115 °F / < 46 °C

Further information on stor-

age stability

The product has an indefinite shelf life when stored properly.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,1,1,2,2,3,4,5,5,5- Decafluoropentane	138495-42-8	TWA	225 ppm 2,320 mg/m ³	WEEL
		STEL	700 ppm 7,217 mg/m ³	WEEL
Trans-Dichloroethylene	156-60-5	TWA	200 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

Vertrel™ MCA specialty fluid



Version 12.5

Revision Date: 04/14/2023

SDS Number: 1327200-00048

Date of last issue: 01/19/2023 Date of first issue: 02/27/2017

ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance

where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Viton®
Glove thickness : 0.7 mm
Wearing time : 120 min

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : ether-like





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : $< -58.0 \, ^{\circ}\text{F} / < -50.0 \, ^{\circ}\text{C}$

Initial boiling point and boiling

range

102 °F / 39 °C (1,013 hPa)

Flash point : Method: Pensky-Martens closed cup

does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

Upper flammability limit

Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit Method: ASTM E681

None.

Vapor pressure : 216 hPa (32 °F / 0 °C)

619 hPa (77 °F / 25 °C)

1,481 hPa (122 °F / 50 °C)

Relative vapor density : 5.4

Density : 1.41 g/cm³ (77 °F / 25 °C)

1.47 g/cm³ (32 °F / 0 °C)

1.35 g/cm³ (122 °F / 50 °C)

Solubility(ies)

Water solubility : 15 g/l (77 °F / 25 °C)

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Viscosity, dynamic : 0.49 mPa.s (77 °F / 25 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 114.428 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 5000 ppm

Test atmosphere: gas

Method: Cardiac sensitization study

Lowest observed adverse effect concentration (Dog): > 5000





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

ppm

Test atmosphere: gas

Method: Cardiac sensitization study

Cardiac sensitisation threshold limit (Dog): > 51,544 mg/m³

Test atmosphere: gas

Method: Cardiac sensitization study

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Trans-Dichloroethylene:

Acute oral toxicity : LD50 (Rat): 7,902 mg/kg

Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): 95.5 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Lowest observed adverse effect concentration (Dog): 250000

ppm

Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 991,309 mg/m³

Test atmosphere: gas

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Trans-Dichloroethylene:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Mild skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Species : Rabbit

Result : No eye irritation





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Method : OECD Test Guideline 405

Trans-Dichloroethylene:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Trans-Dichloroethylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Vertrel™ MCA specialty fluid



Version Revision Date: SDS Number: Date of last issue: 01/19/2023 13.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 415

Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

Trans-Dichloroethylene:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Application Route: Inhalation Method: OECD Test Guideline 414

Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Routes of exposure : Ingestion

Assessment : No significant health effects observed in animals at concentra-

tions of 2000 mg/kg bw or less

Routes of exposure : Skin contact

Assessment : No significant health effects observed in animals at concentra-

tions of 2000 mg/kg bw or less

Routes of exposure : inhalation (vapor)

Assessment : No significant health effects observed in animals at concentra-

tions of 20 mg/l/4h or less

Trans-Dichloroethylene:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Routes of exposure : inhalation (vapor)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

Trans-Dichloroethylene:

Routes of exposure : Inhalation

Assessment : No significant health effects observed in animals at concentra-

tions of 250 ppmV/6h/d or less.

Routes of exposure : Ingestion

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Species : Rat, male and female

NOAEL : 15.463 mg/l LOAEL : 20.618 mg/l Application Route : inhalation (vapor)





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Exposure time : 90 Days

Method : OECD Test Guideline 413

Trans-Dichloroethylene:

Species : Rat, male and female

NOAEL : 4000 ppm LOAEL : > 4000 ppm Application Route : Inhalation Exposure time : 90 Days

Method : OECD Test Guideline 413

Species : Rat, male and female

NOAEL : 3,210 mg/kg
LOAEL : > 3,210 mg/kg
Application Route : Ingestion
Exposure time : 98 Days

Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 13 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 10.6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): > 120 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Scenedesmus capricornutum (fresh water algae)): 120

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1.72 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Vertrel™ MCA specialty fluid



Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Trans-Dichloroethylene:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 135 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 220 mg/l

Exposure time: 48 h

Method: EPA-660/3-75-009

Toxicity to algae/aquatic

plants

: EbC50 (Pseudokirchneriella subcapitata (green algae)): 36.36

mg/l

Exposure time: 48 h

Method: OECD Test Guideline 201

Persistence and degradability

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Trans-Dichloroethylene:

Biodegradability : Result: not rapidly degradable

Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2.4 (75 °F / 24 °C)

Trans-Dichloroethylene:

Partition coefficient: n-

octanol/water

: log Pow: 2.06

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Trans-Dichloroethylene)

Class : 9 Packing group : III

Labels : CLASS 9
ERG Code : 171
Marine pollutant : no

Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE

SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS

THE REPORTABLE QUANTITY.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Trans-Dichloroethylene	156-60-5	1000	2642

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

 1,1,1,2,2,3,4,5,5,5-Decafluoropentane
 138495-42-8

 Trans-Dichloroethylene
 156-60-5

 1,2-Butylene oxide
 106-88-7

California List of Hazardous Substances

Trans-Dichloroethylene 156-60-5

International Regulations

Montreal Protocol : 1,1,1,2,2,3,4,5,5,5-

Decafluoropentane

Additional regulatory information

1,1,1,2,2,3,4,5,5,5- 138495-42-8

Decafluoropentane

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.5645

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

SECTION 16. OTHER INFORMATION


Further information





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Vertrel™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

WEEL : Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average WEEL / STEL : Short term exposure limit

WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of





Version Revision Date: SDS Number: Date of last issue: 01/19/2023 12.5 04/14/2023 1327200-00048 Date of first issue: 02/27/2017

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 04/14/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8